

PART# DC1-AR

# Metal Overhead Garage Door Alarm Sensor



**Acenes**

Innovative Solutions for Security

**Acenes LLC.**

155 Lafayette Ave.

White Plains, NY 10603 US

+914 233 1400

[sales@acenesllc.com](mailto:sales@acenesllc.com)

CE  UL No. BP9463

<b>Name:</b>	Metal Overhead Garage Door Alarm Sensor
<b>Acenes Part:</b>	DC1-AR
<b>Name Memory Aid:</b>	Door contact type 1 with 18" Armored cable
<b>Wires:</b>	2 Wires
<b>Wire Color:</b>	White or Black
<b>Include 1K/1K:</b>	No
<b>Loop Type:</b>	Closed circuit
<b>Number of devices per package:</b>	1
<b>Certification:</b>	CE, UL
<b>Specifications:</b>	UL, CE, RoHS

## Description:

	Part Number: DC1-AR	Part Number: DC1-AR-1K1K
Loop Type	Closed	Closed
Reed Form	N/O, N/C, SPDT	N/O, N/C, SPDT
Contact Color	White or Black	White or Black
Closed Gap (in steel door) [Inch(mm)]	1.5(38)	1.5(38)
Departure Gap (in steel door) [Inch(mm)]	1.65(42)	1.65(42)
Maximum Initial Contact Resistance (Ohm)	0.150	0.150
Maximum Contact Rating (W)	7.5	7.5
Maximum Switching Voltage (VDC/VAC)	100	100
Maximum Switching Current (A)	0.4	0.4

## Features:

- Metal magnetic contacts, ABS body
- Ideal for commercial application or industrial use
- Screws included
- Standard 18" #22AWG leads
- 2 Conductor jacket cable on request
- Armored cable on request
- Longer leads available
- Resistor, Diode and Supervisory Loop available on Request